


TPD Notification(iStick TC40W-GS Tank Atomizer)

Product Photo:				
				
1、 Field Descriptions				
2、 SUBMITTER CHARACTERISTICS				
Field #	Field	Description	Reporting Mandatory (M) or Optional / mandatory fields (F)	To be filled by
	Product-ID-Other-Exist	N/A	M	Eleaf
	Product-ID-Other	N/A	F	Eleaf
	Product-Same-Composition-Exist	N/A	M	Eleaf
	Product-Same-Composition-Exist-Other	N/A	M	Eleaf
	Product-Weight-E-liquid	N/A	F	Eleaf
	Product-Volume-E-liquid	N/A	F	Eleaf
	Product-Manufacturer-Indentification	Shenzhen Eleaf Electronics Co., Ltd.	M	Eleaf
	Product-Site-Address	Area B, 1F, B-28, Heyi Beifang Tech Industrial Park, Shajing Town, Baoan District, Shenzhen, China.	M	Eleaf
	Product-CLP-Classification	N/A	F	Eleaf
	Product_Launch_Date	2015/6/29	M	Eleaf
	Product_Package_Units	1	M	Eleaf

TPD Notification(iStick TC40W-GS Tank Atomizer)

6、PRODUCT DESIGN

Field #	Field	Description	Reporting Mandatory (M) or Optional / mandatory fields (F)	To be filled by
	E-Cigarette_Description	The 'iStick TC40W'(the internal code is EK007) consists of a sealed power and control unit and a removable, refillable e-liquid 'GS TANK' atomizer. The power and control unit consists of an anodized aluminium housing, a lithium polymer single cell battery and a PCB with LED screen to provide a user interface. The 'GS TANK' atomizer consists of a base which accepts the atomizer and provides a connection between the power/control unit and the e-liquid contained within the tank. The upper section of the tank contains the e-liquid which is sealed between itself and the base, as well as supporting a mouthpiece. 1 x GS AIR TC Ni 0.15ohm atomizer head or other GS AIR series atomizer heads are supplied.	M	Eleaf
	E-Cigarette_Liquid_Volume/Capacity	2ml	M	Eleaf
	E-cigarette_Nicotine_Concentration	N/A	F	Eleaf
	E-Cigarette_Battery_Type	Li-ion	F	Eleaf
	E-Cigarette_Battery_Type_Capacity	2600mAh	F	Eleaf
	E-Cigarette_Volt/Watt_Adjustable	both are adjustable	M	Eleaf
	E-Cigarette_Voltage	N/A	F	Eleaf
	E-Cigarette_Voltage_Lower_Range	0.5V	F	Eleaf
	E-Cigarette_Voltage_Upper_Range	8V	F	Eleaf
	E-Cigarette_Wattage	N/A	F	Eleaf

TPD Notification(iStick TC40W-GS Tank Atomizer)

	E-Cigarette_Wattage_Lower_Range	1W	F	Eleaf
	E-Cigarette_Wattage_Upper_Range	40W	F	Eleaf
	E-Cigarette_Airflow_Adjustable	adjustable	M	Eleaf
	E-Cigarette_Wick_Changeable	no	M	Eleaf
	E-Cigarette_Microprocessor	the e-cigarette contains a microprocessor	M	Eleaf
	E-Cigarette_Coil_Composition	Ni -Alloy/Ti -Alloy	M	Eleaf
	Coil Resistance	0.15ohm Ni/0.5 Ti	M	Eleaf
	E-Cigarette-Production-Conformity decl.	<input checked="" type="checkbox"/>	M	Eleaf
	E-Cigarette-Quality -Safety	<input checked="" type="checkbox"/>	M	Eleaf
	Child Tamper Proof decl.	<input checked="" type="checkbox"/>	M	Eleaf
	E-Cigarette_Production _File	attachment	M	Eleaf
	E_Cigarette_Opening/Refill _File	attachment	F	Eleaf
	E-Cigarette -Consistent dosing methods -File	attachment	M	Eleaf
	E-Cigarette -Consistent nicotine -dose/uptake file	attachment	M	Eleaf